

84 Symonds Street
PO Box 5811
Victoria Street West
Auckland 1142 New Zealand
T: +64 9 379 7822 F: +64 9 309 3540
www.marshallday.com

28 February 2024

Goodman PO Box 90940 Victoria Street West Auckland 1142

Attention: Phil Crampsie

Dear Phil

WAITOMOKIA PRECINCT – RESPONSE TO RFI

You have submitted a plan change application to Auckland Council to create a new Auckland Unitary Plan (AUP) Precinct. The new Precinct is called Waitomokia Precinct and is located in Māngere, approximately 3km north of Auckland Airport. Appendix A shows the location plan.

Auckland Council has raised concerns about reverse sensitivity noise effects and has requested a noise assessment to address this. The request is reproduced below:

Please provide a noise assessment which assesses reverse sensitivity effects resulting from the proposed precinct provisions which seek to enable activities sensitive to noise within the plan change precinct area, and if deemed necessary by the assessment, amend the precinct provisions to ensure such effects are adequately addressed inside the plan change precinct area (note: as per AUP Chapter A1.7.3, restricted discretionary activities are generally anticipated by the AUP in the existing environment and this should be reflected in the requested assessment where the proposed precinct provisions seek to apply this activity status to precinct activities sensitive to noise when compared with the underlying Business – Light Industry Zone)

We provide our response in this letter, and we include a list of recommended additions to the Precinct Provisions.

The Precinct proposes to include some noise sensitive activities

Figure 1 overleaf shows the proposed activity table for this Precinct. There are proposed to be four subprecincts, each with a different development intent:

• Sub-precinct A: Land in this sub-precinct is unmodified and would be developed to include typical

light-industrial buildings and uses (i.e. warehouses with associated offices)

• Sub-precinct B: Primary location for development of light industry activities

• Sub-precinct C: Intended to be a town-centre with broader range of commercial and community

activities. This sub-precinct is the focus of our assessment.

• Sub-precinct D: Contains existing buildings and developments. This means that this sub-precinct is

unlikely to see development





Sub-precinct C is proposed to contain activities sensitive to noise¹. All other sub-precincts are not proposed to contain activities sensitive to noise and instead are proposed to contain activities that are anticipated in a *Business – Light Industry* zone. Therefore, typical assessment methods and controls would apply within those sub-precincts.

Figure 1: Activity table from proposed Precinct plan change

Table I0.4.1 Activity table

All sub-precincts

| Activity | | Activity Status | | | |
|---------------|---|--------------------|--|--|--|
| Use | | | | | |
| Accommodation | | | | | |
| (A1) | Visitor accommodation within sub-precinct C | RD | | | |
| Community | | | | | |
| (A2) | Food and beverage up to 1,000m ² in subprecinct C | Р | | | |
| (A3) | Community facilities in sub-precinct C, including within the area show as 'no-build area' on Precinct Plan 3. | | | | |
| (A4) | Recreation facilities in sub-precinct C | Р | | | |
| (A5) | Care centres in sub-precinct C | Р | | | |
| (A6) | Public amenities | Р | | | |
| Commerce | Commerce | | | | |
| (A7) | Offices up to 1000m ² | Р | | | |

AUP Standard E25.6.5 provides the relevant zone noise limit. The noise limit is 65 dB L_{Aeq} , applying at all times, when measured within the boundary of any other site in the *Business – Light Industry* zone. Table 1 overleaf shows our assessment of the potential reverse sensitivity effects due to Sub-precinct C based on this permitted noise level.

¹ Definition of 'Activities sensitive to noise' as per Chapter J of the AUP:

Any dwelling, visitor accommodation, boarding house, marae, papakāinga, integrated residential development, retirement village, supported residential care, care centres, lecture theatres in tertiary education facilities, classrooms in education facilities and healthcare facilities with an overnight stay facility.



Table 1: Acoustic reverse sensitivity assessment table for Sub-precinct C

| Activity code | Activity description | Acoustic assessment of reverse sensitivity |
|---------------|---|---|
| A1 | Visitor accommodation within sub- precinct C | No reverse sensitivity effect because there are already existing noise control measures in AUP Standard E25.6.10. |
| A2 | Food and beverage up to 1,000m² in sub-precinct C | Unlikely to be any reverse sensitivity effects arising from indoor venues. |
| A3 | Community facilities in sub-precinct C, including within the area shown as 'no-build area' on Precinct Plan 3 | Potential for reverse sensitivity effects depending on the use of the community facility. Discussed further below. |
| A4 | Recreation facilities in sub-precinct C | Potential for reverse sensitivity effects depending on the use of the recreation facility. Discussed further below. |
| A5 | Care centres in sub-precinct C | Assuming childcare centres then potential for reverse sensitivity effects. Discussed further below. |
| A6 | Public amenities | No reverse sensitivity effect because public amenities are not noise sensitive. |
| A7 | Offices up to 1000m ² | No reverse sensitivity effect because offices are typical of the zone and compliance at the boundary would ensure an acceptable internal noise level within the office. |

Food and beverage

Australian/New Zealand Standard AS/NZS 2107:2016 'Acoustics – Recommended design sound levels and reverberation times for building interiors' provides recommended internal design levels for food and beverage venues. It recommends that cafeterias, coffee shops, restaurants, and similar establishments are designed to achieve an internal noise level of 40-50~dB L_{Aeq}. Food courts are recommended to achieve an internal noise level of 45~to~55~dB L_{Aeq}.

We consider that with typical façade constructions providing at least 25 decibel of attenuation, the internal noise levels can be readily achieved with windows closed (i.e. 65-25=40 dB L_{Aeq} internal noise level). With windows open and providing at most 15 decibels of attenuation across the façade, we predict that the upper limit of 50 dB L_{Aeq} can be achieved. As such, we predict that there would unlikely be any reverse sensitivity effects from a food and beverage venue. Additionally, this is similar to the existing situation already provided for by Activity Table H17.4.1 (9) in the AUP.

Community and Recreation facilities

Table 2 shows our understanding of the potential use and activities within sub-precinct C. It also shows the recommended internal noise levels from AS/NZS 2107 which we recommend are incorporated into the Precinct Provision.

Table 2: Internal noise levels

| Use | Internal noise levels (dB L _{Aeq}) |
|----------------|--|
| Shop | Up to 55 |
| Libraries | 40 – 45 |
| Function areas | 40 – 45 |
| Pools | 50 – 60 |
| Indoor sports | Up to 45 |



| Use | Internal noise levels (dB L _{Aeq}) |
|--|---|
| Arts and cultural centres | 40 – 45 |
| Places of worship | 30 – 40 |
| Community centres | 40 – 45 |
| Halls | 40 – 45 |
| Marae (maraes are at times used for sleeping). | - |
| | Noise control measures in AUP Standard E25.6.10 |

We consider that the above internal noise levels can be achieved for all relevant venues with windows closed.

For an indoor environment with an upper design noise level of 45 dB L_{Aeq}, the internal noise levels can only be achieved with windows closed which means that a mechanical ventilation system will be required. For shops, pools, and halls, with higher upper design levels, indoor noise levels can be achieved with windows open.

Care centres

We assume care centres relate to early childhood education centres (ECECs). We understand that ECECs are required to have outdoor play areas. The outdoor play areas are required to be exposed to noise levels below 55 dB L_{Aeq (15min)} from external noise sources, both on and off-site (including traffic and nearby industry), at all times of operation including busy periods².

Therefore, an ECEC can give rise to reverse sensitivity effects on neighbouring industrial uses due to the required low external noise level in an outdoor play area compared to the higher permitted noise level of the zone (i.e. 55 dB versus 65 dB).

This can be mitigated by design at the preliminary design stage. For example, the ECEC layout could be such that the outdoor play area is located centrally within a courtyard so that the ECEC's buildings shield it from external noise (within the Precinct and from external sites).

There is no reverse sensitivity effect on Auckland Airport

The Precinct is currently zoned as *Business – Light Industry* (see Appendix B). The plan change does not seek to change the zoning. The zoning maps also shows the Aircraft Noise Overlay in relation to the location plan. Goodman has shown this overlay on their master plan (see Appendix C). We consider that the Aircraft Noise Overlay does not cover any of the proposed building areas. We consider that there will be no reverse sensitivity effect on Auckland Airport.

² ENASS Appendix 4 dated October 2022



We recommend minor additions to the Precinct Provisions

We recommend the Precinct Provisions are updated to include the following:

• Internal noise limit criteria of:

| Use | Internal noise levels (dB L _{Aeq}) |
|--|--|
| Shops | Up to 55 |
| Libraries, Function areas, Arts and cultural centres, Community centres, Halls, Indoor sports | 40 – 45 |
| Pools | 50 – 60 |
| Places of worship | 30 – 40 |

- Where the above internal noise levels can only be achieved with windows closed, then mechanical
 ventilation must be provided to comply, at a minimum, with section G4 of the New Zealand Building
 Code. The mechanical ventilation must be designed to ensure the above internal noise levels are not
 exceeded.
- Care centres must be located and designed to ensure that the outdoor play areas are not exposed to noise above 55 dB L_{Aeq (15min)} noting that the permitted activity noise level of the zone is 65 dB L_{Aeq}.

Yours faithfully

MARSHALL DAY ACOUSTICS LTD

Micky Yang

Acoustician

















| | LOCAT | ION PLA | AN | | | | | |
|---|----------|---------|-------|------|---|---|---------|----------|
| î | 2017 | WAITO | MOKIA | | | | C001 | 2 |
| ١ | INFORMAT | TION | lim | mF . | F | - | 1:10000 | 28.10.22 |



APPENDIX B ZONING



APPENDIX C MASTER PLAN WITH AIRCRAFT NOISE OVERLAY



NOISE CONTOUR
AUCKLAND COUNCIL GEOMAP
SHOWING EXTENT OF
AUCKLAND AIRPORT NOISE
CONTOURS IMPACT ON
WAITOMOKIA SITE

| NEW DATE HEAVERDHIDETALD | COMMUNITY | | |
|---|---|--|--|
| | FLAMMING FOOUS LTD - analyzer regions as ex | | |
| | | | |
| | | | |
| | | | |
| PRINTED 1970/0004 CARDO INI | 10 | | |
| Assessed Terror (2001) - Villa Marrie 2007 I MA POR ICADA POR CAR | | | |

| GOODMAN NZ | |
|-------------------------------|--|
| WAITOMOKIA | |
| 118 Montgomerie Road, Mangere | |



THIS DOCUMENT IS COPYORALITO WILLIAMS ARCHITECTS LTD SO ROTT SOULT VISITED CONTROL TO SOURCE AND ARCHITECTURE AND ARCHITECTUR



| NOISE | CONTO | URS | |
|---------|-------|----------|----------------|
| 2017 | WAITC | MOKIA | C40.4 ~ |
| INFORMA | TION | liming F | 1:2500 RESERVE |